

IDEAL 4305 (TABLE TOP MODEL)

max.
40
mm

Manual office guillotine with 430 mm cutting length and 435 mm table depth (for formats up to A3).


← **43 cm** →

Cutting length	430 mm
Cutting height	40 mm
Narrow cut	34 mm
Table depth	435 mm



optional stand

Technical specifications



Dimensions	400 x 880 x 880 mm (H x W x D) height with stand 1150 mm
Weight	44 kg table top model 54 kg with stand

Product characteristics

SCS - the Safety Cutting System made by IDEAL provides numerous safety features: hinged, transparent safety guard on the front table (locks automatically while cutting); transparent safety cover on the rear table; safety catch (locks blade lever in upper position); safe and convenient blade change from the front without removing machine covers; blade changing device with covered cutting edge; blade depth adjustment from the outside of the machine; cutting stick can be turned or replaced easily from the outside of the machine. Cuts up to 500 sheets of paper (70 g/m²) or bound brochures up to 40 mm. Blade made of German high quality steel. Solid steel blade carrier. Adjustable blade guides made of hardened steel. Patented fast flick action clamp. Side lay with measuring scale (mm/inches). Spindle guided backgauge with hand crank. Fine adjustment of measurement with calibrated scale on the backgauge hand crank. Solid all-metal construction. Designed as table top machine, a stand is available as an option (at an extra cost).

IDEAL

IDEAL 4305 (TABLE TOP MODEL)

Features



TRANSPARENT SAFETY GUARD

A cut can only be executed, if the safety guard is closed and the safety catch for the blade lever is released.



HAND CRANK

The calibrated hand crank and the measuring tape on the side lay ensure the exact positioning of the backgauge.



"FAST FLICK" ACTION CLAMP

Efficient cutting is guaranteed by the "fast flick" action clamp. Insert paper stack, throw the lever to tighten – cut.



BACKGAUGE AND SIDE LAY

The accurate backgauge and side lays are made from cast aluminium and allow precise alignment of the paper stack.



SAFE BLADE CHANGE

Safe and convenient blade change without removing covers. Blade changing device covers cutting edge of blade to protect the operator.



CUTTING STICK CHANGE

Turning or exchanging the cutting stick can easily be managed from the outside of the guillotine without using any tools.



IDEAL

Röntgenvägen 2, Box 1126, 171 22 SOLNA
Tel: 08-445 97 80, Fax: 08-445 97 98
E-mail: info@neopost.se, www.neopost.se